





Техническая памятка



Подложки под ламинированные напольные покрытия компании ЭГГЕР



Материал подложки, толщиной от 1,5 до 3,0 мм и рекомендованным напряжением при сжатии CS 60 кПа (6т/м²) или минимум CS 10 кПа (10т/м²), предназначенный для шумоподавления

Звукоизоляционные подложки подходящие под напольные покрытия ЭГГЕР

Производитель или Дистрибьютор	Марка подложки	Толщина [mm]		
				
EGGER	Silenzio Easy	2,0	✓	✓
EGGER	Silenzio Easy SD	2,0	✓	✓
EGGER	Silenzio DUO	1,5	✓	✓
EGGER	Silenzio Cork	2,0	✓	✓
Solid	Solid green	1,5	✓	✓
Solid	Solid pink	1,8	x	x
Solid	Solid yellow	2,0	x	x
Solid	Solid light green	3,0	x	x
Solid	Solid grey	3,0	x	x
Solid	Solid violet	5,0	x	x
Selit	Selitbloc	1,5	✓	✓
Selit	Ökolit - Kork	2,0	✓	✓
Selit	Selit-Pro Aqua Stop	2,0	✓	✓
Selit	Selitac	2,2	✓	✓
Selit	Selitac	5,0	✓	x
Selit	Selitac Aqua Stop	5,0	✓	x
Selit	Axton - laminate combi underlay	2,0	✓	✓
Sekisui Alveo	ALVEO Professional 140	1,5	✓	✓
Sekisui Alveo	ALVEO PRO+	2,0	✓	✓
Sekisui Alveo	SOUNDPROTECT+ ultra	2,0	✓	✓
Sekisui Alveo	ALVEO Professional Maximum	2,0	✓	✓
Ewifoam	Vinlic Professional PU	1,6	✓	✓
Ewifoam	Vinlay Professional SK	2,1	✓	✓
Ewifoam	Duogard Maxima	2,0	✓	✓
Ewifoam	Duogard Maxima Aquastop	2,0	✓	✓
Ewifoam	Silenzia Standard	2,0	✓	x
Ewifoam	Silenzia Classic	3,0	✓	x
Ewifoam	Silenzia Classic Aquastop Smart	3,0	✓	x
Ewifoam	Universol 1000	1,5	✓	✓
Ewifoam	Universol Alu classic	2,6	✓	✓
Ewifoam	Polytex Aquastop Smart	1,6	✓	x

Производитель или Дистрибьютор	Марка подложки	Толщина [mm]	CLIC it!	
				
Ewifoam	Duogard Professional	2,2	✓	✓
Ewifoam	Duogard strong	2,0	✓	✓
PCI Thomsit	Thomsit TF302	2,0	✓	✓
PCI Thomsit	Thomsit TF303	3,0	✓	✓
Arbiton	Secura	3,0	✓	✗
Arbiton	Secura Aquastop Flex	2,0	✓	✓
WPT	SRL Solid Viscious Gummimatte	1,7	✓	✓
WPT	Natural Sound Basic SD PU mit Alubeschichtung	2,2	✓	✓
WPT	Natural Sound Comfort SD PU mit Alubeschichtung	3,0	✓	✓
Pregis	LBPE Black + PEE	1,3	✓	✓
Steico	Holzfaserdämmplatte	2,5	✓	✗
Dinamik-Izmir	Dyna Foam	3,0	✓	✓
Stiroleks	Stiroleks XPS	3,0	✓	✓
Ebeco	Ebisol	3,0	✓	✗
Taiga	Soundblocker Foam	3,0	✓	✓
Nostra	Nostrasonic Alu EVA mit ALU PET	3,0	✓	✗
Nostra	Nostrasonic Alu EVA mit ALU PET	2,0	✓	✗
Wallmann	No Noise (Warm, silent and stable)	3,0	✓	✗
Kraiburg Relatec	Damtec® Standard	3,0	✓	✓
Сүдафрика	Whisper LAY - beschichtete Gummimatte	2,0	✓	✓
Parquet Directo	Eva Gold Lamina	2,0	✓	✓
Maxeda (Mac Lean)	Sencys Faltmatte grau	3,0	✓	✓
Maxeda (Mac Lean)	Sencys isotac	5,0	✓	✗
MCD	Indicoustic sol	2,0	✓	✗
MCD	Indicoustic sol PV Plus	3,0	✓	✗
MSD	Indicoustic sol PV Ultra	2,0	✓	✓
Amorin	Rollenkork	2,0	✓	✓
Winoe/ Windmüller	Sound Protect Eco SD	2,0	✓	✓
Repac/ 4 Floor	Acoustic Board	1,8	✓	✓
Repac/ 4 Floor	Acoustic Tech	1,3	✓	✓
Repac/ 4 Floor	Acoustic LVT	1,0	✓	✓
Repac/ 4 Floor	XPS Rolle	2,0	✓	✓
Repac/ 4 Floor	Rollenkork	2,0	✓	✓
Austrotherm	PE 2/200 Schwerschaum	2,2	✓	✓
Repac	XPS Platte grau	3,0	✓	✓
Opti- Acoustics Step	Sealed Air Opti-Step 3000	1,2	✓	✓
CMS Danskin Acoustic	Requpol 4515 Multi	3,0	✓	✓
Pliteq	GenieMat RST02	2,0	✓	✓
Pliteq	GenieMat RST03	3,0	✓	✓

Данная техническая памятка составлена с особой тщательностью и соответствует сегодняшнему уровню знаний. Сведения, указанные в данной памятке, основаны на опыте и собственных изысканиях и соответствуют тем знаниям, которыми мы располагаем в настоящее время. Они носят информационный характер и не содержат гарантий относительно характеристик продукции или ее пригодности для определенных сфер применения. Мы не несем ответственность за возможные ошибки, опечатки и неточности при указании норм. Кроме того, возможны технические изменения, вытекающие из постоянного совершенствования продукции EGGGER, а также изменений норм и документов публичного права. Поэтому содержание данной технической памятки не является инструкцией по применению